

IMPASTO



IMPASTO / LOAM / 100-098CB, GESSO / 202-999CB

au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Signature




Carpet Tile




IMPASTO




BISTRE
006-078CB




PUTTY
007-196CB




ALABASTER
007-999CB




GESSO
202-999CB




FLINT
010-007CB




LOAM
100-098CB




PATINA
191-185CB



SIENNA
085-136CB



INDIGO
067-012CB



VERDIGRIS
114-095CB


SPECIFICATIONS

PRODUCT	Impasto
PRODUCT CATEGORY	Carpet Tile
CONSTRUCTION	Multi-Level Loop
YARN/FIBRE	Solution Dyed Nylon
PILE WEIGHT	714g/m ² (21oz)
PILE HEIGHT	4mm
GAUGE	1/10
BACKING THICKNESS	4mm
TOTAL THICKNESS	10.5mm
TILE SIZE	500 x 500mm
TOTAL WEIGHT	5.2kg/m ²
CARTON SIZE	4m ²

BACKING & CUSTOM OPTIONS

COMFI BAK®	In stock
THERMO BAK®	100m ² minimum
SHAPES BY SIGNATURE®	100m ² minimum
FLEXI BAK®	Not Available

INSTALLATION METHODS



PERFORMANCE

DIMENSIONAL STABILITY	<0.15%
ELECTROSTATIC PROPENSITY	<3.0kv
RECOMMENDED ADHESIVE	Refer to our Adhesives Guide
ACCS RATING	Commercial Extra Heavy Duty
WARRANTY	15 year
FIRE RATING ISO 9239.1	>4.5 kw/m ² Critical Radiant Flux Suitable all areas
STAIN/SOIL	Ultra Gard

SUSTAINABILITY

CERTIFICATIONS	GreenTag® GreenRate Level A EPDs & Declare Labels WELL & LBC Eligible
END OF LIFE	Circul8

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two planks are the same. Please note that there may be batch variations from different dye lots.

